

RECEIVED  
CENTRAL FAX CENTER

JUL 11 2006

Serial Number 09/492,273

## AMENDMENTS TO CLAIMS

1. (Currently Amended) A method of initializing a chip card, comprising the steps of:  
inserting a chip card into a processing station, and  
initializing the chip card by having the processing station and the chip card each determine ~~the~~ an secret initial value based on an exchange of parts of first and second values generated, respectively, in the processing station and the chip card, wherein
  - [[--]] first values for determining the secret initial value are generated in the processing station,
  - [[--]] parts of the first values are transmitted to the chip card,
  - [[--]] second values for determining the secret initial value are generated in the chip card,
  - [[--]] parts of the second values are transmitted to the processing station,
  - [[--]] the secret initial value is determined in the processing station from at least parts of the first values and the transmitted parts of the second values, and
  - [[--]] the secret initial value is determined in the chip card from at least parts of the second values and the transmitted parts of the first values.
2. (Previously Presented) A method according to claim 1, characterized in that at least one part of the second values generated in the chip card is generated in accordance with a serial number present in the chip card.
3. (Currently Amended) A method according to claim 1, characterized in that
  - [[--]] the first values generated in the processing station are subjected to a first function,
  - [[--]] the result of the first function is transmitted to the chip card in addition to ~~the~~ a part of the first values generated,
  - [[--]] at least one part of the second values generated in the chip card is subjected to a second function with the transmitted part of the first values,
  - [[--]] the secret initial value is generated in the processing station by means of a third function from the transmitted result of the second function and a ~~part of the first values, in particular the first part of the values not transmitted to the chip card, and~~

**Serial Number 09/492,273**

[[--]] the secret initial value is generated in the chip card by means of a fourth function from the transmitted result of the first function, the transmitted part of the first values and a part of the second values not transmitted to the processing station[[.,]].

4. (Original) A method according to claim 3, characterized in that the first, second, third and fourth functions are identical.

5. (Original) A method according to claim 4, characterized in that the function involves exponentiating a first variable with a second variable and forming a modulo residue to a third variable, the variables corresponding to the first and second values and the first and second results.

6. (Original) A method according to claim 1, characterized in that the secret initial value is a start value for generating random numbers.

7. (Original) A method according to claim 1, characterized in that the secret initial value is a key for encrypting and decrypting data.

8. (Previously Presented) A method according to claim 7, characterized in that the key generated in the processing station and the chip card is used in a personalizing step for encrypting and decrypting further secret keys, which are transmitted from the processing station to the chip card.

9. (Original) A method according to claim 8, characterized in that the key generated in the processing station and the chip card is deleted in the processing station and the chip card after the personalizing step.